

# Material Safety Data Sheet (MSDS)

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- a. Product type : Coated Abrasive Product (YA531)  
 b. Manufacturer : DEERFOS CO.,LTD  
 c. The department of writer : R&D (Research and Development) Center  
 d. Written by : MIN-HO KIM (Mr.)  
 e. The depart of charge : General affairs Dept.  
 f. Address : 10F/ #9-4 84, Yeongdeungpo-ro, Yeongdeungpo-gu, Seoul, Korea (150-101)  
 g. Telephone number : 82-2-780-0046  
 h. fax number : 82-2-780-0045

## 2. HAZARDS IDENTIFICATION

- a. The hazard identification is based on a formalistic procedure as the hazard statements of the ingredients  
 b. The hazard statements of the ingredients are summarized under section 3.  
 c. A greater hazard is the exposure to the dust/fumes from the material or coatings.  
 d. Most of the dust generated during grinding must be evaluated.

## 3. COMPOSITION /INFORMATION ON INGREDIENTS

Composition	CAS No	Conc. (%)	Classification acc. OSHA Hazard Communication	
			Hazard classes / hazard categories	Hazard statements
ALUNDUM	1344-28-1	21		
CALCIUM CARBONATE, NATURAL	1317-65-3	14		
Cryolite	15096-52-3	14	Acute Tox. 4 STOT wdh. 1	H332 H372
PHENOL, POLYMER WITH FORMALDEHYDE	9003-35-4	20	Carc. 1B Acute Tox. 3 Acute Tox. 3 Acute Tox. 3 Skin Corr. 1B Skin Sens. 1	H350 H301 H311 H331 H314 H317
PE / Cotton	-	27		
	-	1~2		

※ Reference

- H350 : May cause cancer  
 H301 : Toxic if swallowed  
 H311 : Toxic in contact with skin  
 H331 : Toxic if inhaled  
 H332 : Harmful if inhaled

H314 : Causes severe skin burns and eye damage

H317 : May cause an allergic skin reaction

H372 : Causes damage to organs through prolonged or repeated exposure

---

#### 4. FIRST AID MEASURES

---

a. Eye Contact

- Do not let the victim rub his eyes.
- Gently rinse the affected eyes with clean water for at least 15 minutes.
- Arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

b. Skin Contact

- Do not absorb through skin. (may cause abrasions)
- Obtain first aid or medical assistance, if needed.

c. Inhalation

- Remove to fresh air.
- Apply artificial respiration as needed.
- Obtain first aid or medical assistance.

d. Ingestion

- Obtain first aid or medical assistance, if needed.

---

#### 5. FIRE FIGHTING MEASURES

---

a. Extinguishing media

- Dry chemical powder, carbon dioxide, water should be used for fires.
- Use extinguishing media appropriate to the source of the fire.

b. Special fire fighting procedures

- Backing & resin binder will burn or decompose, use respiratory protection.

---

#### 6. ACCIDENTAL RELEASE MEASURES

---

No special measures required.

---

#### 7. HANDLING AND STORAGE

---

a. Keep temperature at 0°C - 40°C

b. Keep humidity at 30-60%

c. In use, do not smoke or eat

d. Avoid rough handling or dropping

e. Protect against physical damage

---

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

---

a. Control parameters

- Hazardous dust of the workpiece material may be generated during sanding operations.
- National regulations for dust exposures limit values have to be taken into consideration.
- Observe the regional official regulations.

Substance	CAS-N°	Agency	Threshold limits
alpha- Alumina	1344-28-4	OSHA	TWA: 15mg/m <sup>3</sup> (total dust)
			TWA: 15mg/m <sup>3</sup> ( respirable fraction )
		CMRG	TWA : 1fiber/cm <sup>3</sup>
Cryolite	15096-52-3	ACGIH	TWA (as F): 2.5 mg/m <sup>3</sup>
		OSHA	TWA: 2.5mg/m <sup>3</sup> (total dust)
			TWA (as F): 2.5 mg/m <sup>3</sup>
Formaldehyde	50-00-0	ACGIH	TWA: 0.1mg/m <sup>3</sup>
			STEL : 0.3 mg/m <sup>3</sup>
		OSHA	TWA : 0.75 mg/m <sup>3</sup>
			STEL : 2 mg/m <sup>3</sup>
		NIOSH	TWA : 0.016 mg/m <sup>3</sup>

※ Reference

ACGIH : American Conference of governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor-Occupational Safety and Health Administration

NIOSH : National Institute

TWA : Time-Weighted- Average

STEL : Short Term Exposure Limit

- b. As needed, approved dust respirator.
- c. Wear protective eye glasses or chemical safety goggles.
- d. No precautions other than clean body covering clothing should be needed.
- e. As needed, hearing protection.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

- a. Physical state, form : Solid
- b. Color : Light Brown
- c. Odor : None
- d. Boiling point : N/A
- e. Melting point : N/A
- f. Solubility in water : N/A
- g. Vapor pressure : N/A
- h. Specific gravity : N/A

---

## 10. STABILITY AND REACTIVITY

---

- a. This material is stable.
- b. Hazardous decomposition and polymerization will not occur.
- c. Decomposition products : In use, dust and decomposing resin system fumes are generated. In most cases, the material removed from the work piece will be significantly greater than the coated abrasive product components.

---

## 11. TOXICOLOGICAL INFORMATION

---

- a. Dust may cause respiratory irritation
- b. Rubbing product across the skin may cause mechanical irritation or abrasions.
- c. Dust particles may cause abrasive injury to the eyes.

#### d. Acute Toxicity

Aluminium Oxide	Oral	> 5000 mg/kg (LD50, rat)
	Inhalation	> 7.6 mg/L/h (LC50, rat)
Cryolite	Oral	> 10000 mg/kg (LD50, rat)
	Inhalation	> 200 mg/L (LC50, rat)
	Dermal	> 2000 mg/kg (LD50, rabbit)
Formaldehyde	Oral	> 5000 mg/kg (LD50, rat)
	Inhalation	> 0.578 mg/L/4h (LC50, rat)
	Dermal	> 270 mg/kg (LD50, rabbit)

---

## 12. ECOLOGICAL EFFECTS

---

- This substance is not biodegradable.
- This substance is not bioaccumulate.
- This substance is not fish toxicity.

---

## 13. DISPOSAL CONSIDERATION

---

This combustible material may be burned in a chemical incinerator equipped with on afterburner and scrubber.

---

## 14. TRANSPORT INFORMATION

---


No relevant information found

---

## 15. REGULATORY INFORMATION

---

California Proposition 65 :

 **WARNING** : This product can expose you to Formaldehyde, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---

## 16. OTHER INFORMATION

---

### a. References

- Chemical substances of unknown or variable composition complex reaction products and biological material.
- Coated abrasives modern tool of industry.

### b. Other

- The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof ; however, DEERFOS CO.,LTD. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.
- Please consult DEERFOS CO.,LTD. for further information.

c. Revision Date : 17. July. 2018

d. Revision Number : 2