

# Material Safety Data Sheet (MSDS)

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- a. Product type: Coated Abrasive Products (SA331)
- b. Manufacturer : DEERFOS CO.,LTD
- c. The department of writer : R&D (Research and Development) Center
- d. Written by : Min-ho Kim (Mr.)
- e. The department of charge: General affairs Dept.
- f. Address : 10F/ #9-4 Yangpyeongdong 1ga, Yeongdeungpogu, Seoul, Korea (150-101)
- g. Telephone number : 82-2-780-0046
- h. Fax number : 82-2-780-0045

## 2. HAZARDS IDENTIFICATION

- a. The hazard identification is based on a formalistic procedure as the hazard statements of the ingredients
- b. The hazard statements of the ingredients are summarized under section 3.
- c. A greater hazard is the exposure to the dust/fumes from the material or coatings.
- d. Most of the dust generated during grinding must be evaluated.

## 3. COMPOSITION /INFORMATION ON INGREDIENTS

Composition	CAS No	Conc. (%)	Classification acc. OSHA Hazard Communication	
			Hazard classes / hazard categories	Hazard statements
ALUNDUM	1344-28-1	25~30		
CALCIUM CARBONATE, NATURAL	1317-65-3	16		
Octadecanoic Acid, Zinc Salt	557-05-1	8		
Titanium Dioxide	13463-67-7	2		
BISPHENOL A-EPICHLOROHYDRIN RESIN	25068-38-6	0~5		
PHENOL, POLYMER WITH FORMALDEHYDE	9003-35-4	25~35	Carc. 1B Acute Tox. 3 Acute Tox. 3 Acute Tox. 3 Skin Corr. 1B Skin Sens. 1	H350 H301 H311 H331 H314 H317
Polyester Film	25038-59-9	20		
	-	2~4		

※ Reference

H350 : May cause cancer

H301 : Toxic if swallowed

H311 : Toxic in contact with skin

- H331 : Toxic if inhaled
- H332 : Harmful if inhaled
- H314 : Causes severe skin burns and eye damage
- H317 : May cause an allergic skin reaction
- H372 : Causes damage to organs through prolonged or repeated exposure

---

#### 4. FIRST AID MEASURES

---

- a. Eye Contact
  - Do not let the victim rub his eyes.
  - Gently rinse the affected eyes with clean water for at least 15 minutes.
  - Arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.
- b. Skin Contact
  - Do not absorbed through skin.(may cause abrasions)
  - Obtain first aid or medical assistance, if needed.
- c. Inhalation
  - Remove to fresh air.
  - Apply artificial respiration as needed.
  - Obtain first aid or medical assistance.
- d. Ingestion
  - Obtain first aid or medical assistance, if needed.

---

#### 5. FIRE FIGHTING MEASURES

---

- a. Extinguishing media
  - Dry chemical powder, carbon dioxide, water should be used fires.
  - Use extinguishing medias appropriate to the source of the fire.
- b. Special fire fighting procedures
  - Backing & resin binder will burn or decompose, use respiratory protection.

---

#### 6. ACCIDENTAL RELEASE MEASURES

---

No special measures required.

---

#### 7. HANDLING AND STORAGE

---

- a. Keep temperature at 0°C - 40°C
- b. Keep humidity at 30-60%
- c. In use, do not smoke or eat
- d. Avoid rough handling or dropping
- e. Protect against physical damage

---

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

---

- a. Control parameters
  - Hazardous dust of the workpiece material may be generated during sanding operations.
  - National regulations for dust exposures limit values have to be taken into consideration.

- Observe the regional official regulations.

Substance	CAS-N°	Agency	Threshold limits
alpha- Alumina	1344-28-4	OSHA	TWA: 15mg/m <sup>3</sup> (total dust)
			TWA: 15mg/m <sup>3</sup> ( respirable fraction )
		CMRG	TWA : 1fiber/cm <sup>3</sup>
Titanium Dioxide	13463-67-6	ACGIH	TWA: 10mg/m <sup>3</sup>
		CMRG	TWA : 5 mg/m <sup>3</sup> (raspirable dust)
		OSHA	TWA : 5 mg/m <sup>3</sup> (Total dust)
Formaldehyde	50-00-0	ACGIH	TWA: 0.1mg/m <sup>3</sup>
			STEL : 0.3 mg/m <sup>3</sup>
		OSHA	TWA : 0.75 mg/m <sup>3</sup>
			STEL : 2 mg/m <sup>3</sup>
NIOSH	TWA : 0.016 mg/m <sup>3</sup>		

※ Reference

ACGIH : American Conference of governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor-Occupational Safety and Health Administration

NIOSH : National Institute

TWA : Time-Weighted- Averde

STEL : Short Term Exposure Limit

- b. As needed, approved dust respirator.
- c. Wear protective eye glasses or chemical safety goggles.
- d. No precautions other than clean body covering clothing should be needed.
- e. As needed, hearing protection.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

- a. Physical state, form : Solid
- b. Color : Light Blue
- c. Odor : None
- d. Boiling point : N/A
- e. Melting point : N/A
- f. Solubility in water : N/A
- g. Vapor pressure : N/A
- h. Specific gravity : N/A

---

## 10. STABILITY AND REACTIVITY

---

- a. This material is stable.
- b. Hazardous decomposition and polymerization will not occur.
- c. Decomposition products : In use, dust and decomposing resin system fumes are generated. In most cases, the material removed from the work piece will be significantly greater than the coated abrasive product components.

---

## 11. TOXICOLOGICAL INFORMATION

---

- a. Dust may cause respiratory irritaion

- b. Rubbing product across the skin may cause mechanical irritation or abrasions.
- c. Dust particles may cause abrasive injury to the eyes.

d. Acute Toxicity

Aluminium Oxide	Oral	> 5000 mg/kg (LD50, rat)
	Inhalation	> 7.6 mg/L/h (LC50, rat)
Titanium Dioxide	Dermal	> 10000 mg/kg (LD50, rabbit)
	Inhalation	> 6.82 mg/L/4h (LC50, rat)
	Ingestion	> 10000 mg/kg (LD50, rat)
Formaldehyde	Oral	> 5000 mg/kg (LD50, rat)
	Inhalation	> 0.578 mg/L/4h (LC50, rat)
	Dermal	> 270 mg/kg (LD50, rabbit)

## 12. ECOLOGICAL EFFECTS

- a. This substance is not biodegradable.
- b. This substance is not bioaccumulate.
- c. This substance is not fish toxicity.

## 13. DISPOSAL CONSIDERATION

This combustible material may be burned in a chemical incinerator equipped with on afterburner and scrubber.

## 14. TRANSPORT INFORMATION

No relevant information found

## 15. REGULATORY INFORMATION

California Proposition 65 :

**⚠ WARNING** : This product can expose you to Formaldehyde and Titanoum dioxide, which is known t to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## 16. OTHER INFORMATION

a. References

- Chemical substances of unknown or variable composition complex reaction products and biological material.
- Coated abrasives modern tool of industry.

b. Other

- The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof ; however, DEERFOS CO.,LTD. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.
- Please consult DEERFOS CO.,LTD. for further information.

c. Revision Date : 17. July. 2018

d. Revision Number : 2